



HL-class gas turbines

The next generation of advanced air-cooled gas turbines



The HL-class is paving the way to the next level of efficiency and performance. This evolutionary development step, derived from proven H-class technology, combines a series of new but already tested technologies. The result: A technology carrier to the next level with a combined cycle efficiency beyond 64%.

The HL-class consists of the SGT5-9000HL engine for 50 Hz and the SGT6-9000HL for 60 Hz.



Key technologies

- 1 Evolutionary 3D blading for higher aero-efficiency
- 2 Advanced combustion system for higher firing temperatures and more operational flexibility
- 3 Innovative multi-layer coating for better blade robustness and less cooling-air consumption
- 4 Ultra-efficient internal cooling features for blades and vanes for less cooling air consumption
- 5 Optimized sealings for minimized leakage air
- 6 Large free-standing turbine blade 4 for higher power output



SGT-9000HL series

Performance data for simple cycle operation

	SGT5-9000HL	SGT6-9000HL
Power output	593 MW	440 MW
Fuel	Natural gas, LNG, distillate oil, other fuels on request	
Frequency	50 Hz	60 Hz
GT ramp-up	85 MW/min	85 MW/min
Gross efficiency	>43%	>43.2%
Heat rate	<8,375 kJ/kwh (<7938 Btu/kWh)	<8,333 kJ/kwh (<7898 Btu/kWh)
Turbine speed	3,000 rpm	3,600 rpm
Pressure ratio	24.0 : 1	24.0 : 1
Exhaust mass flow	1,050 kg/s (2,315 lb/s)	725 kg/s (1,598 lb/s)
Exhaust temperature	670 °C (1,238 °F)	670 °C (1,238 °F)
NO _x emissions	Down to 2 ppmvd with SCR	
CO emissions	10 ppm	10 ppm

Performance data for combined cycle operation

	SGT5-9000HL		SGT6-9000HL	
	CC 1x1/1S	CC 2x1	CC 1x1/1S	CC 2x1
Frequency	50 Hz	50 Hz	60 Hz	60 Hz
Gross plant power output	880 MW	1,760 MW	655 MW	1,310 MW
Gross plant efficiency	>64%	>64%	>64%	>64%
Gross plant heat rate	<5,625 kJ/kWh (<5331 Btu/kWh)	<5,625 kJ/kWh (<5331 Btu/kWh)	<5,625 kJ/kWh (<5331 Btu/kWh)	<5,625 kJ/kWh (<5331 Btu/kWh)
Number of gas turbines	1	2	1	2
Pressure/reheat	Triple/yes	Triple/yes	Triple/yes	Triple/yes
Steam temperature	>600 °C (>1,112 °F)	>600 °C (>1,112 °F)	>600 °C (>1,112 °F)	>600 °C (>1,112 °F)

Physical dimensions

	SGT5-9000HL	SGT6-9000HL
Weight (approx.)	497,000 kg (1,095,700 lb)	305,000 kg (672,400 lb)
Length	13.0 m (42.6 ft)	10.8 m (35.4 ft)
Width	5.3 m (17.4 ft)	5.0 m (14.1 ft)
Height	5.5 m (18.1 ft)	4.3 m (14.1 ft)

All ratings are gross values at ISO ambient conditions. Actual performance will vary with project-specific conditions and fuel.

Published by

Siemens Energy Global GmbH & Co. KG
Otto-Hahn-Ring 6
81739 München
Germany

For the U.S. published by
Siemens Energy, Inc.
15375 Memorial Drive, Suite 700
Houston, TX 77079
USA

For more information:

www.siemens-energy.com/gasturbines

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

Siemens Energy is a trademark licensed by Siemens AG.