



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	01	CORRECTED NOTE A PER ECN: 08B0243	7/24/08	DAB/RAB

- △ A) 10.00-300# FF FLANGE CONN-INLET TOP & DISCH. BOTTOM
16-1.00" STUDS ON 15.250 DIA B.C. #17.50 FLANGE.
- B) .25 NPT --- PACKING LUBE CONN ----- TOP
- C) .25 NPT --- PACKING VENT/DRAIN CONN ----- BOTTOM
- D) .75 NPT --- YOKE DRAIN CONN ----- BOTTOM
- E) .25 NPT --- CYL BORE LUBE CONN ----- TOP
- F) .25 NPT --- CYL BORE LUBE CONN ----- BOTTOM
- G) .75 NPT --- YOKE VENT/PURGE CONN (IF REQUIRED) ----- TOP
- H) .38 NPT --- PACKING COOLANT OUT CONN (IF REQUIRED) --- TOP
- J) .38 NPT --- PACKING COOLANT IN CONN (IF REQUIRED) --- BOTTOM
- K) .75 NPT --- CYL COOLANT INLET CONN (IF REQUIRED) --- BOTTOM
- L) .75 NPT --- CYL COOLANT DISCH CONN (IF REQUIRED) --- TOP
- N) .75 NPT --- SPARE CONN ----- TOP OR BOT
- S) .125 NPT --- VVCP ROD PKG VENT TO NON-HAZ AREA ----- TOP
- T) .125 NPT --- GREASE FITTING ----- TOP
- W) .25 NPT --- SCRAPER PURGE CONN (IF REQUIRED) ----- TOP
- X) .25 NPT --- PACKING PURGE CONN (IF REQUIRED) ----- TOP
- AD) .50 NPT --- OUTER END INDICATOR CONN ----- SIDE
- AE) .50 NPT --- FRAME END INDICATOR CONN ----- SIDE
- AJ) .750-10UNC-3B THD, CYLINDER SUPPORT ----- BOTTOM SIDE
- AP) .625-11UNC-3B YOKE SUPPORT ----- BOTTOM
- BB) .75 NPT --- RTD CONN (IF REQUIRED) ----- TOP

20.08
REQUIRED FOR
REMOVAL OF
PISTON & ROD

CLEAR. REQ'D
FOR VALVE
REMOVAL-TYP

TOTAL WEIGHT: APPROX. 5650 LBS

CHG TO: 72 B0 149				
		SIZE	STROKE	TYPE
DRAWN K.DAVISON		16.25	ALL	HOS
CHECKED B.BENNETT		NAME OF PART OUTLINE - 16.25 CYL. W/YOKE VVCP		
APPROVED B.BENNETT		SIZE	FEDERAL SUPPLY CODE	DWG NO.
UG PART		C		HIH01601
SCALE .083:1 WT.			REV.	01
			SHEET 10F1	

DWG NO. HIH01601 SH 1

FORM NUMBER-018